



END STUD ANCHOR 48" ON CENTER
MAXIMUM SPACING TO LIMIT
MOVEMENT BETWEEN WATER
RESISTIVE & AIR BARRIER AND
SEALANT

SUBSTRATE

PAREX USA SHEATHING JOINT
TAPE EMBEDDED IN PAREX USA
WATER-RESISTIVE & AIR BARRIER
COATING

PAREX USA WATER-RESISTIVE &
AIR BARRIER COATING

CLOSED CELL BACKER ROD &
ELASTOMERIC SEALANT (BY
OTHERS)

PAREX USA MESH BACKWRAP

PAREX USA ADHESIVE

EXPANDED POLYSTYRENE
INSULATION BOARD

PAREX USA REINFORCING MESH
EMBEDDED IN PAREX USA BASE
COAT

PAREX USA BASECOAT

PAREX USA PRIMER (OPTIONAL)

PAREX USA FINISH

AT E1.01 INSIDE CORNER TERMINATION

AIRTIGHT SYSTEM

NOTE: To ensure a continuous air barrier across the building envelope, a continuous air seal should be made at each substrate change, joints/gaps, penetrations and dissimilar material terminations. There must be a consideration of the designer in the overall wall assembly design.

Disclaimer: The design, specifications, and construction shall comply with all local building codes and standards. Parex USA installation guidelines are for general information and guidance only and Parex USA specifically disclaims any liability for the use of this design, and for design, engineering, or workmanship of any project. The assembly shall be designed to prevent condensation within the assembly. The designer and the user shall provide final drawings and specifications. Products shown other than those manufactured by Parex USA are shown for clarity of the Parex USA product only. Contact the manufacturer of such other products for installation instructions.